## Linux Installation

• Get the DBSync Linux zip file from the following URL

## http://mydbsync.com/integration/cloud-replication-for-salesforce

• Once the zip file is downloaded to the desired location on your Linux server, navigate to the folder and use the command unzip -d /install-dir dbsync-repl-30-tomcat.zip



• The event manager of the Replication tool can be pointed to a specific directory with the following steps. The below command takes you to the directory path of the event manager of the DBSync Cloud Replication tool.

Σ	root@dbsync:~
<u>File Edit View Search Termin</u>	al <u>H</u> elp
[root@dbsync ~]# vim <mark><dbsync< mark=""></dbsync<></mark>	Home Directory>/dbsync-repl/WEB-INF/db/conf/EventManagerConfig.xml

• The directory path of the event manager is shown below.

М							root	@dbsyr	nc:/ins	stall-d	ir/dbs	ync-r	epl-t	tomcat	-7.0.2	2/dbs	ync-	repl/\	WEB-I	NF/d	lb/co
<u>F</u> ile	<u>E</u> dit <u>y</u>	<u>/</u> iew	<u>S</u> earch	<u>T</u> ermina	il <u>H</u> el	lp															
<eve< th=""><td>ntManag <!--</td--><td>er&gt;</td><td></td><td></td><td></td><th></th><td></td><td></td><th></th><th></th><td></td><td></td><th></th><td></td><td></td><td></td><td></td><th></th><th></th><td></td><td></td></td></eve<>	ntManag </td <td>er&gt;</td> <td></td> <td></td> <td></td> <th></th> <td></td> <td></td> <th></th> <th></th> <td></td> <td></td> <th></th> <td></td> <td></td> <td></td> <td></td> <th></th> <th></th> <td></td> <td></td>	er>																			
	Fol cou	der t Int wh	to store nen syst	e persi: tem is :	sted e shutdo	events own.	(events	s that a	are st	till w	ithin		retry								
	> <persis< td=""><td>tentf</td><td>older&gt;,</td><td>/home/<mark>d</mark></td><td>osync<mark>/</mark></td><th>′temp∕e</th><td>vent_ma</td><td>anager/a</td><th>app<mark>l</mark>/p</th><th>persis</th><td>t<td>siste</td><th>entFo</th><td>lder&gt;</td><td></td><td></td><td></td><th></th><th></th><td></td><td></td></td></persis<>	tentf	older>,	/home/ <mark>d</mark>	osync <mark>/</mark>	′temp∕e	vent_ma	anager/a	app <mark>l</mark> /p	persis	t <td>siste</td> <th>entFo</th> <td>lder&gt;</td> <td></td> <td></td> <td></td> <th></th> <th></th> <td></td> <td></td>	siste	entFo	lder>							
	Fold succ This	ler to essfu fold	) store illy by ler musi	error ( a list) t be di	events ener, fferer		ts that ceed th the pe	could ne max n ersister	not b retry nce fo	be com count older	pleted .) above.										
	> <errore <!--</td--><td>ventF</td><td>older&gt;,</td><td>/home/<mark>1</mark></td><td>osync/</td><th>′temp∕e</th><td>vent_ma</td><td>anager/a</td><th>appl/e</th><th>error&lt;</th><td>/Error</td><td>Event</td><th>tFold</th><td>ler&gt;</td><td></td><td></td><td></td><th></th><th></th><td></td><td></td></errore 	ventF	older>,	/home/ <mark>1</mark>	osync/	′temp∕e	vent_ma	anager/a	appl/e	error<	/Error	Event	tFold	ler>							
	Fold This	ler to fold	) store ler must	succes: t be di	sful e fferer	events. nt from	the fo	older at	bove.												
	> <succes <!--<br-->The the</succes 	sEver max	ntFolden number	of ret	<mark>dbsyn</mark> ries t	the sys	/event_ tem wil	manager	r/appl fy a l	<mark>l/succ</mark>	e <mark>ss</mark> er bef	ore	sEve	entFold	er>						
	>																				

• Directory DBSync must be replaced by the required directory name to point the event manager to that directory.

Σ	root@dbsync:/install-dir/dbsync-repl-tomcat-7.0.22/dbsync-repl/WEB-INF/db/com
<u>F</u> ile <u>E</u> dit <u>V</u> iew <u>S</u> earch <u>T</u> erminal <u>H</u> elp	
<eventmanager> <!--</td--><td></td></eventmanager>	
Folder to store persisted events count when system is shutdown.	(eve <mark>n</mark> ts that are still within max retry
> <persistentfolder>/home,<mark><directory mark="" n<=""></directory></mark></persistentfolder>	ame>/temp/event_manager/appl/persist
Folder to store error events (eve successfully by a listener, and e This folder must be different fro	nts that could not be completed xceed the max retry count.) m the persistence folder above.
<pre><froreventfolder>/home/<directory <!<="" n="" pre=""></directory></froreventfolder></pre>	ame>/temp/event_manager/appl/error
Folder to store successful events This folder must be different fro	m the folder above.
> <successeventfolder>/home/<mark><directory< mark=""> <!--</td--><td>Name&gt;/temp/event_manager/appl/success</td></directory<></mark></successeventfolder>	Name>/temp/event_manager/appl/success
The max number of retries the sy the listener can successfully co	stem will notify a listener before mplete the event.
>	

• Change the permission for the scripts by getting into the *bin* folder and provide executive permission for all the shell scripts using the command *Chmod* 755 \*.sh.

root@localhost:/install-dir/dbs	sync-repl-tomo	at-7.0.22/b	in		×
[root@localhost:dbsync-rd bin CVS DBSync conf dbsync.ico dbsync- [root@localhost:dbsync-rd [root@localhost:bin]#chm [root@localhost:bin]#chm	epl-tomcat-7 -License.txt - <b>repl</b> epl-tomcat-7 od 755 *.sh	7.0.22]#19 Informa <b>lib</b> 0.22]#cc	; htion.txt LICENSE log  bin/	logs NOTICE	RELEASE-NOTES RUNNING.txt
total 2472	- (				
-rw-rr 1 root root -rw-rr 1 root root	28805 Feb 13248 May	19 10:14 7 06:34	<pre>bootstrap.jar catalina.bat</pre>		
-rwxr-xr-x. 1 root root -rw-rr 1 root root	19189 Feb 2168 Feb	19 10:14 19 10:14	<pre>catalina.sh catalina-tasks.xml</pre>		
-rw-rr 1 root root	24239 Feb 200759 Feb	19 10:14 19 10:14	commons-daemon.jar commons-daemon-nati	ive.tar.o	z
-rw-rr 1 root root	2131 Feb 1982 Feb	19 10:14 19 10:14	configtest.bat configtest.sh		
-rw-rr 1 root root drwxr-xr-x. 2 root root	1342 Feb 4896 May	19 10:14 15 13:37	cpappend.bat		
-rwxr-xr-x. 1 root root	7492 Feb	19 10:14 19 10:14	daemon.sh		
-rwxr-xr-x. 1 root root	2021 Feb	19 10:14	digest.sh		
-rw-rr 1 root root	6380 Feb	19 22:46	service.bat		
-rwxr-xr-x. 1 root root	3524 Feb	19 10:14	setclasspath.sh		
-rwxr-xr-x. 1 root root	1960 Feb	19 10:14	shutdown.sh		
-rwxr-xr-x. 1 root root	1961 Feb	19 10:14	startup.sh		
-rw-rr, 1 root root	103936 Feb	19 10:14	tomcat7.exe		
-rw-rr 1 root root	38161 Feb	19 10:14 19 10:14	tomcat-juli.jar		
-rw-rr 1 root root	288166 Feb 4114 Feb	19 10:14 19 10:14	tool-wrapper.bat	JZ	
-rw-rr 1 root root	5086 Feb 2116 Feb	19 10:14 19 10:14	version.bat		
-rwxr-xr-x. 1 root root	1965 Feb	19 10:14	version.sh		

• At this point, the DBSync Cloud Replication tool is installed on your Linux server. You can start the DBSync Cloud Replication tool by navigating to the *bin* folder and running the command from the terminal window ./catalina.sh start.

root@localhost:/install-dir/dbsync-repl-tomcat-7.0.22/bin

<pre>[root@localhost:bin]</pre>	#ls		
bootstrap.jar	commons-daemon.jar	cpappend.bat	digest.sh
catalina.bat	commons-daemon-native.tar.	gz CVS	run.bat
catalina.sh	configtest.bat	daemon.sh	service.bat
catalina-tasks.xml	configtest.sh	digest.bat	<pre>setclasspath.bat</pre>
[root@localhost:bin]	<pre>#./catalina.sh start</pre>		
Using CATALINA_BASE:	/install-dir/dbsync-rep	l-tomcat-7.0.22	
Using CATALINA_HOME:	/install-dir/dbsync-rep	l-tomcat-7.0.22	
Using CATALINA_TMPD	<pre>IR: /install-dir/dbsync-rep</pre>	l-tomcat-7.0.22/t	emp
Using JRE_HOME:	/usr/java/jdk1.7.0_07		
Using CLASSPATH:	/install-dir/dbsync-rep	l-tomcat-7.0.22/b	in/bootstrap.jar:,
<pre>[root@localhost:bin]</pre>	#ps -ef   grep java		
root 3334 1	L 60 09:55 pts/0 00:00:1	5 /usr/java/jdk1.	7.0_07/bin/java -[
erties -Djava.util.	logging.manager=org.apache.	juli.ClassLoaderL	ogManager -Djava.
<pre>bsync-repl-tomcat-7home=/install-dir/d</pre>	.0.22/bin/bootstrap.jar:/in bsync-repl-tomcat-7.0.22 -	stall-dir/dbsync- Djava.io.tmpdir=/:	repl-tomcat-7.0.2: install-dir/dbsyn
root 3366 2594	1 09:56 pts/0 00:00:0	0 grep java	
<pre>[root@localhost:bin]</pre>	#clear		

• To check the logs you can run the command tail --f logs/catalina.out as illustrated in the below screenshot

root@lo	ocalhost:/insta	ll-dir/dbsync-repl-tomca	t-7.0.22			×
[root@	localhost:d	osync-repl-tomcat-7.	0.22]#ls			
bin (	cvs	DBSync-License.txt	Information.txt	LICENSE	logs	RELEASE-NOTES
conf	dbsync.ico	dbsync-repl	lib	log	NOTICE	RUNNING.txt
[root@	localhost:d	osync-repl-tomcat-7.	0.22]#tail -f log	s/catalin	a.out	
Jul 09	, 2013 10:02	2:30 AM org.apache.c	atalina.startup.C	atalina s	tart	
INFO: 1	Server star	tup in 15236 ms				
Jul 09	, 2013 10:03	3:27 AM com.dbsync.f	ramework.event.cu	bbyhole.C	ubbyHole	EventManager\$E
INF0:	Event manage	er is retrying event	S			
Jul 09	, 2013 10:04	4:27 AM com.dbsync.f	ramework.event.cu	bbyhole.C	ubbyHole	EventManager\$E
INF0:	Event manage	er is retrying event	S			
Jul 09	, 2013 10:0	5:27 AM com.dbsync.f	ramework.event.cu	bbyhole.C	ubbyHole	EventManager\$E
INFO:	Event manage	er is retrying event	S			
Jul 09	, 2013 10:00	5:27 AM com.dbsync.f	ramework.event.cu	bbyhole.C	ubbyHole	EventManager\$E
INFO:	Event manage	er is retrying event	S			

• To access the DBSync Cloud Replication console, please paste the http://localhost:8080/dbsync URL in your browser address bar and you will be presented with the DBSync Cloud Replication Home page.

My Account 🗸	■ DBSync Cloud Replication & CDM		🔊 Wiki 🗭 Logout 📰
di Home	Activate your License: L Limited features enabled without		
참 Administration	Getting Started	Help	
	1 Get Started by Connecting to your Application	1 Documentation	
	2 Select your Objects	2 Wiki	
	3 Schedule your Backup	a Contact Us	
	Profiles		Add Profile
	Name App		Action
	test Salesforce		🕮 Delete
	DBSync Cloud Replication & CDM 6.7 © 2020		

To stop DBSync Cloud Replication, navigate to the bin folder and execute the script ./catalina.sh stop from the terminal window and to check the status of process execute the command ps --ef / grep java as shown below.

<pre>[root@localhost:bin]#./catalina.sh stop</pre>
Using CATALINA_BASE: /install-dir/dbsync-repl-tomcat-7.0.22
Using CATALINA HOME: /install-dir/dbsync-repl-tomcat-7.0.22
Using CATALINA TMPDIR: /install-dir/dbsync-repl-tomcat-7.0.22/temp
Using JRE_HOME: /usr/java/jdk1.7.0_07
Using CLASSPATH: /install-dir/dbsync-repl-tomcat-7.0.22/bin/b
[root@localhost:bin]#ps -ef   grep java
root 3402 2594 0 09:57 pts/0 00:00:00 grep java
[root@localhost:bin]#